

Synthetic rope technologies

Addressing the mooring industries evolving requirements

Rui Pedro Faria, Greg Mozsgai,
Christof Dewijngaert

16/07/2022

BRIDON
SYNTHETICS

Confidentiality

This document remains the exclusive property of NV Bekaert SA.

Communication thereof is wholly confidential and does not extend beyond the technical staff of the addressee, who is not authorized to duplicate this document nor to make known to a third party any contents thereof.

NV Bekaert SA is exclusively entitled to apply for a patent for any patentable element contained in this document.

NV Bekaert SA disclaims all liability which may arise out of the putting into use of the information contained in this document, provided it did not assume control thereof. It also disclaims all liability for infringements of industrial property rights which may arise out of the putting into use of the information contained in this document.

All the information contained in this document is based on reasonable research, but does not guarantee any result.

The Bridon you probably know

Spiral Strand Deepwater Mooring

BRIDON




Bridon Neptune Quay, UK



FLNG Prelude



FOW Tampen



Bridon Synthetics ... growing beyond steel

BRIDON
SYNTHETICS




Grangemouth, UK



Mining



Synthetic lifting




Deepwater mooring




Shallow water mooring

Mooring technology – evolving continuously

Mooring as we know it




A new agenda emerging



- Shallow water renewables requirements
 - Higher dynamic loads
 - Reduced footprints
 - Even tighter cost effectiveness
 - Step change in supply rhythm
 - Preload as norm
 - Platform stability
 - Cut resistance
 - Fouling
 - Seabed contact

Bridon MoorLine

- Bridon Synthetics MoorLine rope consists of:
 - Core of multiple, parallel laid sub-ropes
 - Polyester, Nylon or HMPE fibres
 - Braided jacket
 - High performance fabric filter
 - Binds structure of the rope together and protects the core and filter



Mooring rope technology

- High tenacity Polyester
 - 20+ years of proven performance and reliability
 - Mid range stiffness characteristics
- Low creep HMPE:
 - Suitable for TLP moorings due to its high tensile strength and high stiffness
 - Lifetime can be engineered for 25 years, in accordance to predicted load scenario
 - Lower weight and easier installation when compared to steel
- High tenacity Coated Nylon
 - Next slide

Mooring rope technology

- High tenacity Coated Nylon
 - Lower stiffness than polyester to reduce dynamic loads
 - Fatigue performance
 - Testing demonstrates much longer fatigue life than previous reported in literature
 - Field data from renewable energy demonstrators confirms results from laboratory
 - Currently executing DNV Qualification of Technology to ensure safe use of MoorLine Nylon in permanent mooring of FOWT

Mooring rope technology

- Solving the existing/new challenges

Cut resistance




Fouling



Mooring rope technology

- Solving the existing/new challenges
 - Example: leeward line on floater, as shown below.



Fouling

- Fouling growth most severe in shallow waters
- Negative impact
 - Additional weight and drag changing mooring dynamics over time
 - Difficult to measure fouling weight and volume (see next slide)
 - Line retrieval process removes much
 - Ingress of hard shell sea life into the rope core
 - 5 micron filters proven effective
- Cleaning is possible
 - Available technologies
 - Mechanical: brushes, cutters, knives
 - Water jet
 - Durability is key



Seabed contact

- For synthetic fibre ropes, on tension and previously tensioned ropes are not normally allowed to contact the seabed.
 - Shallow waters and high static loading a challenge for designers
- Ropes capable of seabed contact simplify for complex mooring systems (buoys, etc.)



Seabed contact

■ Particle ingress

- Major reduction of rope life demonstrated
- Most projects require a protection against particle ingress
 - Typically stipulate a filter layer with *“protection against particle of 5µm and larger”*.

■ External Abrasion


- Due to repetitive seabed contact the jacket can wear or rupture
- Exposure of core -> Reduced service life
 - Reduced particle ingress resistance (damage filter layer)
 - Damage to sub-ropes (in extreme cases)



Cut resistance

- FWT farms will attract fisherman...
 - Fishing lobbies strong at many FWT sites “lines must be over trawlable”
 - Current safety perimeters are insufficient to protect lines
 - Mooring footprint typically much larger than safety zone
 - Fishermen will “cut the corner”
- Cut resistance is synthetics enabler?
 - Line/cluster failure can lead to power cable rupture
- “only defined requirement available in the industry is Statoil (Equinor) requirements to cut-resistant jackets” – DNV
 - Based on simulations from Aasta Hansteen platform
 - single point cutting, worst case vessel speed/size combo

BRIDON
SYNTHETICS



Seabed contact / Cut resistance

- **Advanced Composite Structure**

An enhanced protection layer has been developed, that combines the know characteristics of the Polyester Braided Jacket with a polymeric matrix. This creates a composite structure that addresses the main failure mechanisms that were identified from seabed contact field trials:

- High abrasion resistance
- High tear resistance
- High elongation (low/no effect axial stiffness)
- Chemically inert
- Long lifetime

- **Cutting protection is also based on the same platform**

- Composite structure enables adding different levels of cut protection


- **Testing of Jacket composite structure**

- Lab tests and field trials made to confirm the suitability of the protection layer.
- Seabed drag testing conducted vs. base case Moorline rope.
 - Specimens were repeatedly dragged, lifted/dropped, and abandoned
 - Damage due to abrasion and particle ingress of each rope was documented..

- **Currently under discussion with class societies and lead users**

Integral floatation


- Why is buoyancy needed:
 - Keep rope off sea bed (e.g. Fouling weight, Leeward lines)
 - Modify mooring response
 - Inverse catenary
- Effective, economical solution developed compatible with all other line features
 - Fully integrated (protected), flexible and scalable
 - Drastic reduction in component count.



Integral floatation

■ BBRG integral floatation solution

- Compact design fully integrated into the rope
- Rigid foam certified for sub-surface use
- High foam density for maximizing floatability
- Can be placed in specific locations of the rope – distributed buoyancy
- Reduces number of mooring line components
- Rope keeps its bending stiffness (bendable/spoolable)
- Different foam thickness available to meet buoyancy requirements
- Increases the rope overall diameter (depends on the amount of floatation needed), which increases size of transportation reels



Industrial grade rope terminations



- Human-factor
- Labor and time intensive
- Splice setting variation



- Industrial process
 - Higher output
 - Easier to scale (Industry 4.0)
 - Subrope condition monitoring functionality
 - Reducing human factor variation
 - Suitable hardware substrate for **monitoring**



100% Strength efficiency
100% length accurate
100% repeatable



We're wondering...

- What do you see as major opportunities for synthetic mooring ahead? What are major obstacles?
- Any shallow water developments relevant in deepwater?
- Accelerating innovation in a low volume low risk market?



BRIDON · BEKAERT
THE ROPES GROUP